



ProCuity™ bed series

Brilliance in a bed

Our safest and most intelligent bed yet, ProCuity features low height for all patient care environments, advanced fall prevention technologies, and is the only truly wireless bed on the market today. ProCuity offers a proactive approach to help prevent falls, reduce injury from falls, and streamline caregiver workflow. It's also versatile – accommodating clinical needs from Med/Surg units up to the ICU, helping hospitals standardize their bed fleet and improve caregiver efficiencies.



L model

11.5" low height
4" screen



LE model

11.5" low height
Electric brakes
USB outlet



Z model

14" low height
Zoom Motorized Drive



ZM model

Premium 8" screen
Powered mattress
integration ability

Specifications

ProCuity Specifications

Model number	3009
---------------------	------

Width

42 in (106.6 cm)

Height range (to litter top) L and LE models

High: 30 in (76.2 cm)

Low: 11.5 (29.2 cm)

Height range (to litter top) Zoom versions

High: 32 in (81.3 cm)

Low: 14 in (35.6 cm)

Litter positioning

Fowler: 0° to 65° ±5°

Gatch: 0° to 30° ±5°

Trend./Reverse Trend.: +12° to -10° ±5°

Patient Surface

84 in x 35 in (213.4 cm x 88.9 cm)

Patient Surface with bed extender:

96 in x 35 in (243.8 cm x 88.9 cm)

Caster Diameter:

6 in (15.2 cm)

standard features

- Bed scale*
- 3-zone Adaptive Bed Alarm
- iBed Watch
- Auxiliary outlets
- Battery back-up
- Integrated bed extender
- Nurse call interface
- Pendant port
- Manual brakes
- Patient belongings holder
- Wireless capability
- Motion interrupt
- Integrated Foley hook
- Integrated restraint hooks
- Automatic under-bed light
- Integrated Pump holder
- 3-position siderails
- Smart Prompts and Safety Dashboard

Electronic specs

- Agency approvals: UL approved to IEC 60601
- Volts: 100-240 VAC
- Ampere rating: 8A
- Current leakage: Not more than 300 μ A (microamps)
- Frequency: 50/60 Hz
- Hospital grade plug: 120 VAC, 60 Hz, 8A

*±3 lb (1.4 kg) of total patient weight for patients who weigh 60 lb (27.2 kg) to 100 lb (45.4 kg) and ± 3% of the total patient weight for patients who weigh 100 lb (45.4 kg) to 550 lb (249.5 kg)

Stryker reserves the right to change specifications without notice.

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: iBed, ProCuity, Secure Connect, Zoom, Stryker. All other trademarks are trademarks of their respective owners or holder.

Mkt Lit-2077 07 OCT 2020 Rev B
Copyright © 2020 Stryker

3800 E. Centre Avenue
Portage, MI 49002 USA
t: 269 329 2100
toll free: 800 327 0770

stryker.com